Specification sheet



QSB5-G3 EU Stage IIIA / EPA Tier 3 / TA Luft Compliant



Description

The QSB5 incorporates the latest diesel engine technology, including a high pressure common rail fuel system for greater fuel efficiency, lower noise and reduced emissions.

Features

Full-Authority Electronic Controls - Optimize engine operation and deliver critical information for controlling costs, reducing maintenance and seamless integration with other components.

Holset HX35 Wastegated Turbo - Wastegated design optimizes transient response.

Low-Maintenance Fuel Filter Assembly - The fuel filter incorporates an integral water separator and water-in-fuel sensor; 500-hour filter life with easy top-load replacement using standard Fleetguard® filters.

Coolpac Integrated Design - Products are supplied complete with cooling package and air cleaner kit for a complete power package. Each component has been specifically developed and rigorously tested for G-Drive products, ensuring high performance, durability and reliability.

Service and Support - G-Drive products are backed by an uncompromising level of technical support and after sales service, delivered through a world class service network.



This engine has been designed in facilities certified to ISO9001 and manufactured in facilities certified to ISO9001 or ISO9002.

Our energy working for you.™ ©2019 Cummins Inc. | QSB5-G3 (4/19)



1500 rpm (50 Hz ratings)

Gross engine output			Net engine output		Typical generator set output						
Standby	Prime	Base	Standby	Prime	Base	Standb	y (ESP)	Prime	(PRP)	Base	(COP)
kWm/BHP			kWm/BHP		kWe	kVA	kWe	kVA	kWe	kVA	
94/126	81/109	74/99	86/115	74/99	67/90	72	90	66	82	62	78

1800 rpm (60 Hz ratings)

Gross engine output		Net engine output		Typical generator set output							
Standby	Prime	Base	Standby	Prime	Base	Standb	y (ESP)	Prime	(PRP)	Base	(COP)
	kWm/BHP			kWm/BHP		kWe	kVA	kWe	kVA	kWe	kVA
108/145	94/126	84/113	96/129	83/111	73/98	80	100	72	90	68	85

General engine data

Туре	4 cycle, in-line, 4 cylinder diesel		
Bore mm	107 mm (4.21 in.)		
Stroke mm	124 mm (4.88 in.)		
Displacement litre	4.5 litre (275 in. ³)		
Cylinder block	Cast iron, 4 cylinder		
Battery charging alternator	100 amps		
Starting voltage	24 volt, negative ground		
Fuel system	Direct injection		
Fuel filter	Dual spin-on fuel filters with water separator		
Lube oil filter type(s)	Spin-on full flow filter		
Lube oil capacity (I)	12.2		
Flywheel dimensions	SAE3		

** @ 13 mm H₂0

Fuel consumption 1500 (50 Hz)

%	kWm	BHP	L/ph	g/kWh				
Standby Power								
100	94	126	25	6.7				
Prime Pow	Prime Power							
100	81	109	22	5.9				
75	61	82	18	4.7				
50	41	55	12	3.2				
25	20	27	6	1.7				
Continuous Power								
100	74	99	21	5.6				

Fuel consumption 1800 (60 Hz)

%	kWm	BHP	L/ph	g/kWh				
Standby Power								
100	108	145	29	7.7				
Prime Power								
100	94	126	26	6.9				
75	70	95	21	5.6				
50	47	63	15	3.9				
25	23	32	8	2.2				
Continuous Power								
100	84	113	24	6.2				





Weights and dimensions

Length	Width	Height	Weight (dry)
mm	mm	mm	kg
821	739	982	

Ratings definitions

Emergency Standby	Limited-Time Running	Prime Power (PRP):	Base Load (Continuous)
Power (ESP):	Power (LTP):		Power (COP):
Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel Stop power in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power to a constant electrical load for limited hours. Limited-Time Running Power (LTP) is in accordance with ISO 8528.	Applicable for supplying power to varying electrical load for unlimited hours. Prime Power (PRP) is in accordance with ISO 8528. Ten percent overload capability is available in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power continuously to a constant electrical load for unlimited hours. Continuous Power (COP) in accordance with ISO 8528, ISO 3046, AS 2789, DIN6271 and BS 5514.



For more information contact your local Cummins distributor or visit power.cummins.com



Our energy working for you.™

©2019 Cummins Inc. All rights reserved. Cummins is a registered trademark of Cummins Inc. PowerCommand, AmpSentry, InPower and "Our energy working for you." are trademarks of Cummins Inc. Other company, product, or service names may be trademarks or service marks of others. Specifications are subject to change without notice. QSB5-G3 (4/19)